Contents

Abstract **vi**

Acknowledgements **v**

1 Introduction **1**

1.1 General overview 1

1.2 This thesis in the context of probabilistic PBD 2

1.3 The organization of this thesis 5

2 A Technical Framework for Probability-based (DCFD) Seismic Formats **8**

2.1 Abstract 8

2.2 Introduction 8

2.3 Sources of uncertainty in engineering problems 9

2.4 Document map 10

2.5 Foundation development 10

2.5.1 Structural limit states 11

2.5.2 Structural demand variable (state variable) 11

2.5.3 Structural capacity variable (Limit state variable) 11

2.5.4 Limit state probability 12

2.5.5 General solution strategy 12

2.5.6 Ground motion intensity measure 14

2.5.7 Randomness: The only source of variability 14

2.5.7.1 Spectral acceleration hazard 15

2.5.7.2 Median relationship between S_a and drift demand 16

2.5.7.3 Annual frequency of exceeding demand – Drift hazard 18

2.5.7.3.1 Numerical example 25

2.5.7.4 Annual frequency of exceeding a limit state 28

2.5.7.4.1 Numerical example: 32

2.5.7.5 Limit state frequency, the IM-based approach 34

2.5.8 Randomness and uncertainty as the sources of variability 36

2.5.8.1 Spectral acceleration hazard: 37
2.5.8.2 Probability of exceeding a drift demand value – Drift hazard 40
2.5.8.2.1 Numerical example 46
2.5.8.3 Annual probability of exceeding a limit state 48
2.5.8.3.1 Numerical example 52
2.5.8.4 Limit state frequency: the IM-based approach 54
2.5 Summary 56
2.6 Acknowledgements 56

3 Probability-based Design (DCFD) Seismic Formats 57
3.1 Introduction 57
3.2 Randomness: The only source of uncertainty 58
3.2.1 Spectral acceleration corresponding to a demand equal to d 59
3.2.2. Spectral acceleration ${}^{P_0}s_a$ for a hazard level equal to P_0 60
3.2.3 DCFD Format 61
3.2.3.1 Displacement-based demand 64
3.2.3.2 Displacement-based capacity 65
3.2.3.3 Demand factor 65
3.2.3.4 Capacity factor 66
3.2.3.5 Factored demand and demand hazard 66
3.2.3.6 General Form for the DCFD design format 67
3.2.3.7 Numerical Example 68
3.2.4 Fragility/Hazard Format – An IM-based probabilistic format 73
3.2.4.1 Hazard curves 75
3.2.4.2 Fragility curves 76
3.2.4.3 The IM-based limit state frequency and fragility/hazard 77
3.2.4.4 Numerical Example 78
3.3 Randomness and uncertainty, the sources of uncertainty 79
3.3.1 A confidence-based DCFD format 81
3.3.1.1 Numerical Example 86
3.4 Summary and conclusions 87
3.5 Acknowledgements 88

4 Alternative Nonlinear Demand Estimation Methods for Probability-Based Seismic Assessment 89

4.1 Abstract 89

4.2 Keywords 90

4.3 Introduction 90

4.4 A Comprehensive assessment example 92

4.5 Record selection 94

4.6 Probabilistic framework for design and assessment of structures 95

4.7 Drift hazard - the annual frequency of exceeding drift demand 96

4.8 Demand and capacity factored design format 97

4.9 Site-specific hazard curve: estimation of k value 100

4.10 Evaluation of factored demand by numerical integration 100

4.11 Narrow-range methods 103

4.11.1 Single-stripe analysis 103

4.11.2 Cloud analysis 107

4.11.3 Cloud analysis scaled 111

4.11.4 Narrow-range methods for a lower spectral acceleration 113

4.12 Wide-range methods 115

4.12.1 Multiple-stripe analysis (MSA) 116

4.12.2 Incremental dynamic analysis 118

4.12.2.1 Capacity estimation using the results of IDA 121

4.12.3 Evaluation of factored capacity by numerical integration 123

4.13 Number of Records 124

4.14 Summary and Conclusions 126

4.15 Acknowledgements 129

5 Probability-Based Seismic Assessment: Non-linear Dynamic Displacement Estimation in the Region of Global Instability 130

5.1 Abstract 130

5.2 Introduction 131

5.3 Organization of this chapter 132

5.4 Global dynamic instability capacity (collapse) estimation 134

5.5 Spectral acceleration hazard 135

5.6 Probability distribution of demand for a given spectral acceleration 135

5.6.1 A Three-parameter distribution and its percentiles 137

5.6.2 Methods incorporating the three-parameter distribution 139
5.6.2.1 Fully parametric using power-law functions 139
5.6.2.2 Fully parametric using the IDA procedure 141
5.6.2.3 Semi-parametric using multiple-stripe analysis 144
5.6.2.4 Pseudo-parametric method 146
5.6.2.5 Comparison of the fully-parametric IDA method to semi-parametric with MSA 146
5.6.3 Non-parametric methods 147
5.6.3.1 Non-parametric considering the collapse cases 147
5.6.3.2 Non-parametric not considering the collapse cases 148
5.6.3.3 Comparison of the non-parametric methods considering and not considering the collapse cases 148
5.6.3.4 Comparison of the non-parametric method not considering collapse and semi-parametric method with MSA 149
5.6.3.5 Discussion 149
5.7 Drift hazard 151
5.7.1 Estimating drift hazard by disaggregating into collapse and non-collapse parts 151
5.7.1.1 Drift hazard estimation in limiting cases 151
5.7.2 Non-parametric calculation of drift hazard 152
5.7.3 Semi-parametric calculation of drift hazard 153
5.7.4 Fully parametric (closed-form) evaluation of drift hazard 154
5.7.5 Discussion 157
5.8 Factored Demand 157
5.8.1 Non-parametric using the non-parametric drift hazard 158
5.8.2 Fully-parametric using IDA procedure with simple DCFD 158
5.8.3 Factored demand: Semi-parametric using parametric IDA curves 160
5.8.4 Factored demand: Semi-parametric using single and double-stripe analysis 161
5.8.5 Discussion 166
5.9 Factored capacity 167
5.10 Practical Applications 167
5.11 Summary and Conclusions 168
5.12 Acknowledgements 170

6 Non-linear Response Dependence on Ground Motion Characteristics with Implications for Ground Motion Record Selection 171

6.1 Abstract 171

6.2 Keywords 173

6.3 Introduction 173

6.4 Records used in this chapter 176

6.5 Ground motion characteristics 177

6.6 The spectral acceleration and the spectral shape factor 177

6.7 Maximum inter-story drift angle: The displacement-based response 178

6.8 Residual-residual plot 179

6.9 Establishing sufficiency based on the un-scaled set of records 181

6.9.1 System with long first-mode period: LA 20 story Results 182

6.9.2 System with short period: Generic SDOF structure 188

6.10 Studying the dependence of the displacement-based response given $S_a(T_{FM})$ on the spectral shape factor at period T, $R(T, T_{FM})$ 193

6.10.1 System with large first-mode period: LA 20 story Results 194

6.10.2 SDOF systems with short period 196

6.11 Discussion: Correlation between spectral-shape factor and magnitude 198

6.12 Discussion: Does magnitude matter? 202

6.13 Observations for the SDOF system with a different yield strength 203

6.14 Observations for LA 20 story building when the ground motion records are scaled 206

6.15 Sufficiency and ground motion record selection 210

6.16 Investigating the sufficiency of PGA as the intensity measure with respect to magnitude 214

6.17 Adjusting for possible dependencies using weighted regression 216

6.18 Summary and conclusions 221

6.18.1 Limitations 223

6.19 Acknowledgments 224

7 Conclusions 225

7.1 Summary and conclusions 225

7.1.1 Chapter 2 225

7.1.2 Chapter 3 226

7.1.3 Chapter 4 227

7.1.4 Chapter 5 228
7.1.5 Chapter 6 229
7.2 Limitations and future work 230

Appendix A **233**

Appendix B **235**

Appendix C **236**

Bibliography **238**